

Water Treatment

BFS FILTERS

BFS FILTERS FOR EMBARKING & DELIVERING OF WATER: suitable for filtration of fresh and sea water in marine application and industry. Mounted on stainless steel stand or with mounting brackets.

- BFS 1: one filter housing with single or double filtration cartridge 10" or 20"
- BFS 2: two filter housings with filtration cartridges 10" or 20"
- BFS 3: three filter housings with double filtration cartridges 10" or 20"

For the BFS 2 and BFS 3 we suggest to combine a single or double filtration cartridge (BIG BLUE) and one with activated carbon. The BFS series can be used also as oil/water separator with coalescent cartridges. The flow rate may vary depending on the feed pressure and the cartridge type.



BFS 1 20"

BFS 3 20"



R30-20"-BB:
30 µm
filtration

DGD-5005-20"-BB:
2-stages filtration,
50 & 5 µm filtration

EPM-20"-BB:
activated carbon,
10 µm filtration

CP5-20"-BB:
5 µm
filtration



BC-10" & 20"-BB:
oil-water
separator

R30-10":
30 µm
filtration

P5-10":
5 µm
filtration

FILTER CARTRIDGES MADE IN U.S.A.



TECHNICAL DATA

Model	Max flow rate per hour (litres/gallons)	Fittings (inch)	Dimensions (mm) -L x W x H-	Weight (kg)
BFS 1 10"	9,000 / 2,377	1/4"- 3/8"- 1/2"- 3/4"	130 x 150 x 370	4
BFS 2 10"	9,000 / 2,377	1/4"- 3/8"- 1/2"- 3/4"	280 x 150 x 370	6
BFS 3 10"	9,000 / 2,377	1/4"- 3/8"- 1/2"- 3/4"	420 x 150 x 370	8
BFS 1 10"-BB	16,000 / 4,227	1"- 1 1/2"	190 x 220 x 400	5
BFS 2 10"-BB	16,000 / 4,227	1"- 1 1/2"	380 x 220 x 400	8
BFS 3 10"-BB	16,000 / 4,227	1"- 1 1/2"	580 x 220 x 400	12
BFS 1 20"-BB	16,000 / 4,227	1"- 1" 1/2	190 x 220 x 670	7
BFS 2 20"-BB	16,000 / 4,227	1"- 1" 1/2	380 x 220 x 670	10
BFS 3 20"-BB	16,000 / 4,227	1"- 1" 1/2	580 x 220 x 670	14